



ARFU 26

Compaction of in-situ concrete: 6,000 1/min.



Quality exposed concrete surface to satisfy high expectations. ARFU 26

First-class compacted concrete is essential for the production of concrete surfaces. Thanks to its high-quality construction, Wacker Neuson's external vibrator ARFU 26 with integrated frequency inverter offers this precision compaction. The result: Beautifully smooth and level concrete surfaces on walls, pillars and columns.

- Extremely versatile thanks to its integrated frequency inverter
- Can be connected directly to single-phase electric current.
- Long durability thanks to its powerful electric motor with stable speeds
- Available for all standard voltages and frequencies
- Fast assembly thanks to easy to use fastening clamps



Technical specifications

	ARFU 26/6/230	ARFU 26/6/115 UK
Vibrations rpm	6,000	6,000
Centrifugal force max. kN	3.47	3.47
Voltage V	220-240	110-130
Rated current A	6	12
Weight kg	11.2	11.2
L x W x H mm	232 x 227 x 103	
Fastening	90 x 125	90 x 125

* plus 2 meters supply cable

Please note

that product availability can vary from country to country. It is possible that information / products may not be available in your country. More detailed information on engine power can be found in the operator's manual; the stated power may vary due to specific operating conditions.

Subject to alterations and errors excepted. Applicable also to illustrations.

Copyright © 2015 Wacker Neuson SE.